

RECESSED DOOR TO RECEIVE DRYWALL Model RDW

DATE



KARP ASSOCIATES, INC.

260 Spagnoli Road Melville, NY 11747 (631) 768-8300 - Phone (631) 768-8350 - Fax

SPECIFICATIONS

GENERAL SCOPE:

Sizes shall be as indicated on the drawings.

CONSTRUCTION:

- 1. Frame shall be 16 gauge steel and doors shall be 16 gauge steel.
- 2. Door shall be recessed 0.625".
- 3. Trim shall be galvanized steel dry wall bead.
- 4. Hinge shall be concealed pivoting rod type.
- 5. Locks shall be flush and screwdriver operated with cam and studs, or shall be key operated cylinder lock with automatic dust shutter.
- 6. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel.

STANDARD SIZES

DOOR SIZE	WALL/CEILING	NUMBER OF	SHIP WT.
H X W (IN.)	OPENING (IN.)	LATCHES	(LBS.)
12 x 12	12 1/8 x 12 1/8	1	7.4
18 x 18	18 1/8 x 18 1/8	2	12.8
24 x 12	24 1/8 x 12 1/8	2	12.5
24 x 24	24 1/8 x 24 1/8	4	19.4
36 x 24	36 1/8 x 24 1/8	5	29.0

PROJECT DATA				
Project Name:				
Architect:				
Contractor:				
Agent/Customer Name:				
Tagging Instructions:				
Special Instructions:				

PROJECT SCHEDULE							
Qty.	Н	w	No. of Latches	Finish	Remarks		

5/8" LONG STAINLESS STEEL STUDS

GALVANIZED

H + 2"

