

Extra Heavy Eastern Pattern Snatch Block

- Model 4102V Steel Shells with Steel Sheaves
- Drop-Forged Fittings
- Bronze, Self-Lubricating Bushings
- Galvanized Finish
- Features A Steel Sleeve Over A Steel Pin for Increased Strength and Durability
- Combination Score to Handle Variety of Sizes of Wire and Manila Rope
- Working Loads are Resultant Working Loads
- DO NOT EXCEED THE WORKING LOAD LIMIT





Catalog	UPC No.	Block	Fitting	Manila Rope	Wire Rope	Sheave	Sheave Size -	Bearing	Sheave Size -	Working Load	Weight
No.	020418	Size	Type	Diameter	Diameter	Size - OD	Rim Thickness	Diameter	Center Pin Dia.	Limit (Metric Tons)	Each
7336624	123849	6 in	Swivel Hook w/ Latch "V"	7/8 in	3/8 in	3 in	1-1/8 in	1 in	1/2 in	2 t	10.00 lb

Lineman's Snatch Block, 5022

- Model 5022
- For Stringing Light Conductor Cable
- Hook Fits Around Insulator Pin or in the Insulator Hole
- Can Be Driven Into A Pole or Cross Arm
- Available with Bronze Self-Lubricating (SL) Bushings or Roller Bushed Bearings
- Available with or Without Hook

Catalog No.	UPC No. 020418	Fitting Type	Rope Size	Finish	Bushing Type	Weight Each
7380601	129834	Hook	3/4 in	Galvanized	Roller Bushed	2.50 lb
7380602	129841	Hook	3/4 in	Galvanized	Bronze Bushed, SL	2.50 lb
7380603	129858	None	3/4 in	Galvanized	Bronze Bushed, SL	2.22 lb



Hand Line Utility Block, CHB300 / CHB303

- Model CHB300 / CHB303
- For Stringing Conductor Cable or Fiber Rope Applications
- Side Opening Block with Zinc Plated Swivel Hook with Safety Latch
- CHB300 features Ultra-lightweight Block and Sheave Molded From Rugged Reinforced Nylon Fiberglass High Di-Electric Material and 1,000 lb. Safe Working Load Limit
- CHB303 features Lightweight Aluminum Alloy Block and Sheave Construction with Permanently Lubricated Sheave and Safety-tethered Locking Pin and Strongest in Class 1,500 lb. Safe Working Load Limit
- 3" Sheaves Blocks Can Accommodate Rope Through 5/8" Diameter
- Design Factor: 3 to 1



