



## PULLS



### 9

#### Oval Wrought Door Pull

Certification: Meets ANSI A156.6 for J401 Pulls

Base: 1/2" x 3/4" (13 mm x 19 mm)

Projection: 2" (51 mm)

Clearance: 1-1/2" (38 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US32, US32D

Fasteners: Two (2) 1/4-20 x 2-1/4" FPHMS with finish washers

Handicap:

- 2-1/2" (64 mm) clearance available on special orders
- Add prefix "H" to number (i.e., H9E)

Options:

- May be combined with a plate to make a pull plate
- Other centers on special order

Notes:

- For sizes or finishes not listed in this catalog, contact Hager Customer Service for availability
- Not suitable for back to back mounting

| CTC Length  | 9E  | 9G  | 9J  | 9L  |
|-------------|-----|-----|-----|-----|
| Inches      | 6   | 8   | 10  | 12  |
| Millimeters | 152 | 203 | 254 | 305 |



### 10

#### Round Pull

Certification: Meets ANSI A156.6 for J401 Pulls

Base Diameter: 1-1/4" (32 mm)

Projection: 3" (76 mm)

Clearance: 1-3/4" (45 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Aluminum, brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D

Fasteners: Two (2) 5/16-18 FPHMS with finish washers

Handicap:

- 2-1/2" (64 mm) clearance available on special orders
- Add prefix "H" to number (i.e., H10L)

Options:

- May be combined with a plate to make a pull plate
- Other centers on special order

Notes:

- If ordered with tempered glass, specify glass thickness and hole size
- For sizes or finishes not listed in this catalog, contact Hager Customer Service for availability
- Back to back - see model 20

| CTC Length  | 10L | 10Q |
|-------------|-----|-----|
| Inches      | 12  | 18  |
| Millimeters | 305 | 457 |



### 11

#### Round Offset Pull

Certification: Meets ANSI A156.6 for J402 Pulls

Base Diameter: 3/4" (19 mm)

Projection: 2-1/2" (64 mm)

Offset: 2-1/2" (64 mm); 90° Standard

Clearance: 1-3/4" (45 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Aluminum, brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D

Fasteners: Two (2) 5/16-18 x 2-1/4" FPHMS with finish washers

Handicap:

- 2-1/2" (64 mm) clearance available on special orders
- Add prefix "H" to number (i.e., H11E)

Options:

- For 45° offset, add prefix "X" to number (i.e., X11E)
- Other centers available on special orders

Notes:

- If ordered with tempered glass, specify glass thickness and hole size
- For sizes or finishes not listed in this catalog, contact Hager Customer Service for availability
- Back to back - see model 21

| CTC Length  | 11E | 11G | 11J | 11L |
|-------------|-----|-----|-----|-----|
| Inches      | 6   | 8   | 10  | 12  |
| Millimeters | 152 | 203 | 254 | 305 |