



RESIDENTIAL



212

Hinge Pin Door Bumper

- Materials: Zinc alloy base
 Finishes: US3, US4, US5, US10A, US10R, US15A, US15, US26, US26D, ABA
 Notes:
- Non-marking white plastic tip
 - For use where standard door stops are not desirable
 - For use with narrow trim
 - Adjustable from 80 degrees to 120 degrees
 - For use with residential hinges
 - Works with 1/4" (6 mm) hinge pins



1412

Door Guard

- Arm Length: 4 (102 mm)
 Materials: Zinc alloy base
 Finishes: U3, US4, US5, US10A, US15A, US15, US26, US26D, ABA
 Fasteners: Seven (7) #6 x 3/4" FPHWS
 Notes:
- Provides extra security from inside door
 - Limits door opening when latch is thrown
 - Poly bag (1 each) with screws



1413

Flush Bolt

- Faceplate: 3/4" x 6" (19 mm x 181 mm)
 Strike: 7/8" x 1-3/4" (22 mm x 45 mm)
 Bolt Diameter: 1/2" (13 mm)
 Bolt Throw: 15/16" (24 mm)
 Bolt Backset: 7/16" (11 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, US5, 10A, 10R, US15A, US15, US26D, ABA, AN
 Fasteners: Four (4) #6 x 3/4" FPHWS
 Notes:
- Poly bag (1 each) with strikeplate and screws
 - Square corners



1414

Flush Bolt

- Faceplate: 3/4" x 6" (19 mm x 181 mm)
 Strike: 7/8" x 1-3/4" (22 mm x 45 mm)
 Bolt Diameter: 1/2" (12.7 mm)
 Bolt Throw: 15/16" (24 mm)
 Bolt Backset: 7/16" (11 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, US5, 10A, 10R, US15A, US15, US26, US26D, ABA, AN
 Fasteners: Four (4) #6 x 3/4" FPHWS
 Notes:
- Poly bag (1 each) with strikeplate and screws
 - Rounded corners