3800 Series Escutcheon

Grade 1 Mortise Escutcheon

Notes:

- Self-adjusting case for beveled doors
- Stopworks are incorporated in thumbturn
- Breakable spindles to prevent lock from unlocking or being damaged
- Non-handed, stainless steel, deadlocking bar
- Concealed thru-bolts
- Field reversible
- Conventional cylinder, SFIC housing and LFIC housing available
- Heavy duty commercial, industrial, institutional
- BHMA Certified Grade 1, Series 1000, Security with standard mortise cylinder

PRODUCT SPECIFICATIONS

STANDARD DOOR PREP:
- 3-5/8" (92 mm) Center of cylinder to spindle
- 2-7/16" (62 mm) Center of thumbturn to spindle

CERTIFICATIONS:
- BHMA Certified ANSI A156.13, Series 1000, Grade 1, Operational and Security
- ADA Compliant ANSI A 117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours for "A" label single doors
- UL 10C Positive Pressure Rated
- Lifetime warranty
- A250.13 Severe Windstorm Resistant (must specify)

EXPOSED TRIM:
- Cast zinc - standard
- Forged brass, cast stainless steel optional

LOCK CASE:
- 4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)

ARMOR FRONT:
- 1-1/4" x 8" x 7/32" (32 mm x 203 mm x 5 mm) - Standard
- 1-1/16" x 8" x 7/32" (27 mm x 203 x 5 mm) - Optional

ESCUTCHEON:
- 1-15/16" X 8" (50 mm X 203 mm)

KEYS:
- Two operating keys supplied per lock

CYLINDERS:
- Brass - Keyed different - C keyway
- Other keying options, including keyed 6-pin, available from factory
- Drilled 6-pin, keyed 5-pin - Standard
- Small Format Interchangeable Core cylinder option available
- SFIC uncombinated or combinated, brass 6- or 7-pin sold separately
- Large Format Interchangeable Core cylinder option available
- LFIC zero bitted or combinated, brass 6-pin sold separately
- Schlage "L" cam is used standard on Hager mortise lock

HANDING:
- Shipped LHR; easily field reversible

DOOR THICKNESS:
- 1-3/4" - 2-1/2" (45 mm - 64 mm)
- 1-3/4" - 2" (45 mm - 51 mm) for Privacy Function (3840, 3844, 3896)
- Must specify door thickness if greater than1-3/4" (45 mm)

BACKSET:
- 2 3/4" (70 mm) Only

LATCHBOLT:
- 3/4" (19 mm) Throw with anti-friction tongue, all stainless steel

DEADBOLT:
- 1" (25 mm) Throw, Stainless Steel

STRIKE:
- 3985 1-1/4" x 4-7/8" (32 mm x 124 mm), 1-3/16" (30 mm) Lip - Standard

FASTENERS:
- Thru-bolted trim concealed under escutcheon

FINISHES:
- US3, US4, US10, US10B, US26, US26D, US32D*
- * For a true US32D finish, must specify stainless steel levers

* Withnell, William, and Archer are the only lever styles available with stainless steel option.
- US3, US4, US10, US10B, US26 subject to extended lead time

FUNCTIONS:
- 10 - Passage, 17 - Dummy, 27 - BTB Dummy, 40 - Privacy, 44 - Privacy w/ Coin turn, 50 - Office, 53 - Entry, 56 - Corridor, 57 - Classroom Security, 61 - Apartment, 70 - Classroom, 80 - Storeroom, 81 Storeroom w/ Deadlock, 82 - Institution, 96 - Privacy w/ Indicator

OPTIONS:
- Tactile warning
- Lead lining
- Split finish

LEVER OPTIONS:
- Archer, August, Charles, Johnston, Joshua, Louis, Warren, William, and Withnell levers