



ADVANCED CABLE TIES PART NUMBER		+	A N (mm) /005 127mm)	B IN (mm) +/005 (.127mm)	C IN (mm) +/005 (.127mm)	D IN (mm) +/005 (.127mm)	E IN (mm) +/005 (.127mm)	F IN (mm) +/005 (.127mm)	G IN (mm) +/005 (.127mm)	H IN (mm) +/005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY	
Al	AL-MT4A250-N-C		.990 (25.146mm)		.160 (4.064mm)	.058 (1.473mm)	.530 (13.462mm)	.071 (1.803mm)	.252 (6.401mm)	.117 (2.972mm)	.310 (7.874mm)	RED/NYLON	22-18	UL/CSA
A	AL-MT4B250-N-C		.990 (25.146mm)		.190 (4.826mm)	.086 (2.184mm)	.535 (13.589mm)	.071 (1.803mm)	.252 (6.401mm)	.117 (2.972mm)	.310 (7.874mm)	BLUE/NYLON	16-14	UL/CSA
Al	AL-MT4C250-N-C		1.150 (29.210mm)		.234 (5.943mm)	.144 (3.658mm)	.656 (16.662mm)	.071 (1.803mm)	.252 (6.401mm)	.117 (2.972mm)	.310 (7.874mm)	YELLOW/NYLON	12-10	UL/CSA
		ADVANCED CABLE TIES INC.												
					ADVANCED CABLE TIES – DOUBLE CRIMP NYLON INSULATED N DISCONNECTS								D MALE	
								COLOR: RED, BLUE & YELLOW NYLON						
								SHEET 1 OF 1 REV.: A			DRAWING NO.: DC-NY-M-DIS-A			
А	6/25/14	JA	KT	KT	INTITIAL RELEASE			DRAWN B	Y	DATE	CHECK	CHECK SCALE		
REV	DATE	ВҮ	СНК	APPROVE	DESCRIPTION		JA		5/25/14	KT	NONE			
			THIS DRA	AWING IS PR	OVIDED ON A R		Onfidential Pro Is and is not to			•	TERESTS OF ADV	ANCED CABLE TIES,	INC.	