


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-07-50-ID-9	.47 (12.0mm)	1.81 (46.0mm)	7.913 (201.000mm) +/- .098 (2.500mm)	6.614 (168.000mm) +/- .059 (1.500mm)	.180 (4.580mm) +/- .012 (.300mm)	.512 (13.000mm) +/- .017 (.430mm)	1.098 (27.900mm)	.056 (1.140mm) +/- .010 (.250mm)	50 (222)	V-2	
AP(R, L)-07-50-ID-0	.47 (12.0mm)	1.81 (46.0mm)	7.913 (201.000mm) +/- .098 (2.500mm)	6.614 (168.000mm) +/- .059 (1.500mm)	.180 (4.580mm) +/- .012 (.300mm)	.512 (13.000mm) +/- .017 (.430mm)	1.098 (27.900mm)	.056 (1.140mm) +/- .010 (.250mm)	50 (222)	V-2	
AP(R, L)-14-50-ID-9	.47 (12.0mm)	3.77 (96.0mm)	13.625 (346.075mm) +/- .098 (2.500mm)	13.250 (336.550mm) +/- .059 (1.500mm)	.187 (4.750mm) +/- .012 (.300mm)	.511 (12.979mm) +/- .017 (.430mm)	1.067 (27.102mm)	.055 (1.397mm) +/- .010 (.250mm)	50 (222)	V-2	
AP(R, L)-14-50-ID-0	.47 (12.0mm)	3.77 (96.0mm)	13.625 (346.075mm) +/- .098 (2.500mm)	13.250 (336.550mm) +/- .059 (1.500mm)	.187 (4.750mm) +/- .012 (.300mm)	.511 (12.979mm) +/- .017 (.430mm)	1.067 (27.102mm)	.055 (1.397mm) +/- .010 (.250mm)	50 (222)	V-2	
						 ADVANCED CABLE TIES, INC.					
						ADVANCED CABLE TIES – 50 LB (222n) IDENTIFICATION SERIES CABLE TIES					
						COLOR DESIGNATIONS:		MATERIAL:			
						0 = BLACK 9 = NATURAL		NYLON 6/6 POLYAMIDE			
C	4/27/17	JA	KT	KT	NEW LOGO ADDED.		SHEET 1 OF 1	REV.: C		DRAWING NO.: ID-C	
B	2/11/16	JA	KT	KT	CORRECTION TO E DIMENSION ON 14-50 TIES		DRAWN BY	DATE	CHECK	SCALE	
A	12/23/14	JA	KT	KT	INITIAL RELEASE		JA	4/27/17	KT	NONE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	4/27/17	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.