



# WireSert Locking

Diameter Thread Pitch

4-48

Tang



0.224

Suggested Drill Bit Size

0.1200 (#31)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	5340-01-022-2325	DRAWN	NAME	DATE
MILITARY STANDARD	MS21209-F0420	CHECKED		
TH. STANDARD: ANSI/ASME		ENG APPR.		
ACRONYM: UNF		MFG APPR.		
ROTATION: Right-Hand		Q.A.		
MATERIAL FINISH	Stainless Steel 18-8	COMMENTS:		
PART NUMBER	35L7C-C8K4-00420-34			
NEXT ASSY	USED ON			
APPLICATION	DO NOT SCALE DRAWING			



**17-B KENTUCKY AVENUE  
PATERSON, NEW JERSEY 07503  
TEL: 973-684-4010 FAX: 973-684-3095  
email: TechSupport@industrialhardware.com  
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
<b>A</b>		
SCALE: 1:8	WEIGHT: 0.04	SHEET 1 OF 1