




WireSert Locking

ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

Diameter Thread Pitch

1-12

Tang



Suggested Drill Bit Size  1.0156 (1-1/64)

2

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

		MILITARY STANDARD MS21209-F1 620	DRAWN	NAME	DATE
			CHECKED		
			ENG APPR.		
		TH. STANDARD: ANSI/ASME ACRONYM: UNF ROTATION: Right-Hand MATERIAL FINISH Stainless Steel 18-8	MFG APPR.		
			Q.A.		
NEXT ASSY	USED ON	PART NUMBER 35L7C-C8K4-10020-0F	COMMENTS:		
APPLICATION	DO NOT SCALE DRAWING				



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE: 1:8	WEIGHT: 1.25	SHEET 1 OF 1