


# WireSert Locking

Diameter Thread Pitch

M22 x 1.5

Tang



55mm

Suggested Drill Bit Size 0.8906 (57/64)



ZONE		REV.	DESCRIPTION	DATE	APPROVED

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

				NAME	DATE
				DRAWN	
				CHECKED	
				ENG APPR.	
				MFG APPR.	
				Q.A.	
				COMMENTS:	



**17-B KENTUCKY AVENUE  
PATERSON, NEW JERSEY 07503  
TEL: 973-684-4010 FAX: 973-684-3095  
email: TechSupport@industrialhardware.com  
www.industrialhardware.com**

NEXT ASSY	USED ON	AEROSPACE MA3329-275 TH. STANDARD: ISO Metric ACRONYM: ISO ROTATION: Right-Hand MATERIAL FINISH Stainless Steel 18-8 PART NUMBER 35L7C-C8M2-C22J25-0F
APPLICATION		DO NOT SCALE DRAWING

SIZE <b>A</b>	DWG. NO.	REV.
SCALE:1:8	WEIGHT: 0.837	SHEET 1 OF 1