Architectural ACCESS DOOR

The Babcock-Davis Architectural Access Door is built with the architect in mind. Constructed with an industry-standard steel door, the updated design further improves on strength and aesthetics.

FEATURES

ANTI-FLEX FRAME Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.

PAINLESS INSTALLATION When mounting screws are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.

OPTIONAL STAINLESS STEEL The spot free design on the face of the door gives an aesthetically pleasing appearance.



MATERIALS





Powder Coat

Stainless Steel







Plaster Bead

LATCHES

Cam Latch





Key Operated

Cam Lock



Mortise

Lock Prep



Knurled Knob

DETAILS

DOOR

- BNT/BNW: 16 gage Steel
- BNP: 14 gage Steel
- 16 gage Type 304 Stainless Steel

FRAME

- 16 gage Steel
- 16 gage Type 304 Stainless Steel

SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or Wall

FLANGE 1 inch Exposed, Drywall Bead or Plaster Bead

HINGE Concealed Spring Button

PAN DEPTH 1/2 inch

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X L	ENGTH	OPT	IONS
BN				x			
	T 1 inch Flange	c Screwdriver Cam	Standard Sizes (W x L)		в	Galvannealed	
	W Drywall Bead	Latch		16" x 20" 18" x 18"	24" x 36" 24" x 48"	D14	14 gage Steel Door
	P Plaster Bead	L Key operated Cam Lock	10" × 10"	18" x 24"	30" x 30"	G	Gasketing
		M Mortise Lock	12" x 12" 12" x 18"	20" x 30" 22" x 22"	30" x 36" 32" x 32"	в	Louvered Door
		(1-1/8") Prep	12" x 24" 14" x 14"	22" x 30" 24" x 24"	36" x 36"	М	Masonry Anchors
		N Knurled Knob		24 x 24 24" x 30"		s	Type 304 Stainless Steel

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.