Top Security

ACCESS DOOR

Babcock-Davis' Top Security Access Door is manufactured with detention-grade materials and provides access through openings in walls. The pan style access door includes a heavy-duty butt hinge welded on the surface of the door to prevent unwanted access.

DETAILS

DOOR 7 gage Steel

FRAME 3/16 inch Steel Angle - 2 inches by 2 inches

• Min: 8 inches by 8 inches

• Max: 48 inches by 54 inches

INSTALLATION Wall

FLANGE Exposed

HINGE Surface Mounted Heavy-Duty Butt

PAN DEPTH 1-1/4 inch

FINISH White Powder Coat



ORDER GUIDE

BASE	LATCH	WIDTH	Χ	LENGTH	OPTIONS
BTS			X		
	D Detention Lock Prep M Mortise Lock (1-1/8") Prep S Security Screws				G Gasketing M Masonry Anchors S Type 304 Stainless Steel

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information. *Recommended for Wall surfaces only.

Draft Stop

ACCESS DOOR

Babcock-Davis' Draft Stop Door is a non-rated access door designed to provide access through wall openings in the attics where draft stop conditions are needed. This self-closing and self-latching access door allows for access from both sides of the door.

DETAILS

DOOR 14 gage Steel (self-closing)

FRAME 16 gage Steel

- Min: 6 inches by 6 inches
- BDT Max: 24 inches by 72 inches, 36 inches by 60 inches or 48 inches by 48 inches
- BDW Max: 36 inches by 48 inches

INSTALLATION Wall

FLANGE Exposed or Drywall Bead

• BDT: Flush Continuous Piano • BDW/BDP: Concealed Pin

FINISH White Powder Coat



ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	Х	LENGTH	OPTIONS
BD				х		
	T 1 inch Flange W Drywall Bead P Plaster Bead	D Detention Prep K Knurled Knob/ Key Operated Latch Bolt M Mortise Lock (1-1/8") Prep		22" x 30 24" x 24	24" x 40"* 24" x 48"*	B Galvannealed G Gasketing S Type 304 Stainless Steel

 $Rough\ opening\ is\ door\ size\ +1/4\ inch\ minimum.\ Additional\ sizes\ available,\ call\ for\ more\ information.$ *Recommended for Wall surfaces only.