


1279

Five Knuckle
Plain Bearing
Standard Weight

Application:

- ANSI A8133
- Non-rising removable pin with button tip and plug
- With door closer use ball bearing hinge
- For use with medium frequency doors or doors requiring low frequency service



PRODUCT SPECIFICATIONS

MATERIAL:

- Steel with Steel pin

FINISHES:

- LS, H2H, USP, US3, US4, US10, US10A, US10B, US15, US26, US26D

OPTIONS:

- NRP - Non-removable pin

PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (MACHINE)	SCREW SIZE (WOOD)
2 x 2	51 x 51	0.083	4	-	3/4 x 8
2 1/2 x 2 1/2	64 x 64	0.089	6	-	3/4 x 8
3 x 3	76 x 76	0.097	6	-	1 x 9
3 1/2 x 3 1/2	89 x 89	0.119	6	1/2 x 10-24	1 x 9
4 x 4	102 x 102	0.129	8	1/2 x 12-24	1 1/4 x 12
4 1/2 x 4	114 x 102	0.134	8	1/2 x 12-24	1 1/4 x 12
4 1/2 x 4 1/2	114 x 114	0.134	8	1/2 x 12-24	1 1/4 x 12
5 x 4	127 x 102	0.145	8	1/2 x 12-24	1 1/4 x 12
5 x 4 1/2	127 x 114	0.145	8	1/2 x 12-24	1 1/4 x 12
5 x 5	127 x 127	0.145	8	1/2 x 12-24	1 1/4 x 12
6 x 4 1/2	152 x 114	0.160	10	1/2 x 1/4-20	1 1/2 x 14
6 x 5	152 x 127	0.160	10	1/2 x 1/4-20	1 1/2 x 14
6 x 6	152 x 152	0.160	10	1/2 x 1/4-20	1 1/2 x 14