

THIS SIDE UP FOR LHR DOOR

# 4700 RIM PANIC RATED EXIT DEVICE STANDARD TEMPLATE (FOR PANIC RATED DEVICES ONLY)

(REV: 01)  
DWG NO: T-ED00317

FOLD HERE  
**CAUTION**  
DO NOT USE DOOR EDGE!

PLACE THIS SIDE ON FRAME STOP  
PLACE THIS SIDE ON DOOR

(2x) METAL: DRILL/TAP FOR 1/4"-20  
MACHINE SCREWS.  
WOOD: PRE-DRILL 1/8" HOLES.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS  
TRIM OR SEXBOLTS: DRILL 5/16" CLEARANCE HOLE  
ON PUSH SIDE, 3/8" HOLE ON PULL SIDE  
WOOD: PRE DRILL 1/8" HOLES

FOR TRIM DRILL 1/2" CLEARANCE HOLE.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS  
WOOD: PRE-DRILL 1/8" HOLES  
SEXBOLTS: DRILL 5/16" CLEARANCE HOLE ON PUSH SIDE,  
3/8" HOLE ON PULL SIDE.

2 1/2"  
[64]

2 7/8"  
[73]

Ø OF DEVICE AND STRIKE

3/8"  
[10]

1 3/16"  
[30]

1 7/16"  
[37]

19/32"  
[15]

DRILL/TAP FOR 1/4"-20  
AND INSTALL SCREW  
AFTER FINAL ADJUSTEMENTS.

AFTER EXIT DEVICE IS CUT AND  
MOUNTED, INSTALL END CAP  
BRACKET CENTERED ON DEVICE Ø

40" [1016]  
RECOMMENDED HEIGHT MAY BE  
DETERMINED BY DESIGN SPEC'S

29/32"  
[23]  
ADJUST FOR  
BEST FIT

2 1/4"  
[57]

FINISHED FLOOR  
//////

 HOLE LOCATIONS

PRIMARY DIMENSIONS SHOWN IN INCHES,  
DIMENSIONS IN [ ] ARE MILLIMETERS.

THIS SIDE UP FOR RHR DOOR

